APPENDIX H

THE POLLUTANT REMOVAL CAPACITY OF POND AND WETLAND SYSTEMS: A REVIEW

THE POLLUTANT REMOVAL CAPACITY OF POND AND WETLAND SYSTEMS: A REVIEW

			\$0.	Sign 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	Solve Area (i)	10,11,00,00	1/2	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	Z.				/5/
Dry E	xtended Detentio	n											
1	Lakeridge	VA	28	88.0	0.00	0	•	8	0	0	8	8	⊗
2	London Commons	VA	27	11.4	0.22	•	•	8	•	8	0	•	•
						•	•	8	•	8	•	•	•
3	Stedwick	MD	25	34.0	0.30	•	0	8	•	8	•	•	•
4	Maple Run III	TX	17	28.0	0.50	0	0	8	•	•	•	•	⊗
5	Oakhampton	MD	16.8		0.50*	•	•	8	8	8	8	8	⊗
6	None Given	KS	19	12.3	3.42	0	0	0	8	0	0	•	•
Wet P	Ponds												
7	Seattle	WA	5	0.75	1.		•	8	⊗	8	•	•	
8	Boynton Beach	FL	8		1	•	8	•	⊗		⊗	8	⊗
9	Grace Street	MI	18	ĺ	** 0.52	•	0	8	0	8	8	•	⊗
10	Pitt-AA	MI	6	4872.0	** 0.52	•	0	8	8	0	•	•	
11	UnquaNY		8		**10.70	•	•	8	8	8	8	•	⊗
12	Waverly Hills	MI	29	}	** 7.57	•	•	8	•	•	•		•
13	Lake Ellyn	IL	23		**10.70		•	8	8	8	8	•	•
14	Lake Ridge	MN	20	315.0	0.08		•	0	•	0	⊗	•	⊗
							•	0	•	0	8	•	⊗
15	West Pond	MN	8	76.0	0.15	•	•	8	8	•	8	•	•

Key:

0 to 20% Removal 20 to 40% Removal

40 to 60% Removal

● 60 to 80% Removal ● 80 to 100% Removal

Manager insufficient Knowledge

Key:

TSS Total Suspended Solids

TP Total Phosphorus

SP Soluble Phosphorus

TN Total Nitrogen

N03 Nitrate

COD Chemical Oxygen Demand

P6 Lead

Zn Zinc

Note: An Asterisk (*) denotes an inferred value Note: (**)Denotes Volume of Basin/Volume of Runoff

Note: The table above provides summary data on the pollutant removal capability of nearly sixty stormwater pond and wetland systems. Each study differs with respect to pond design, number of storms monitored, pollutant removal calculation technique, and monitoring technique, so exact comparisons between studies are not appropriate.

Note: The information in the above table was taken from: A Current Assessment of Urban Best Management Practices -Techniques for Reducing Non-Point Source Pollution in the Coastal Zone, prepared by: Metropolitan Washington Council of Governments, March 1992.

THE POLLUTANT REMOVAL CAPACITY OF POND AND WETLAND SYSTEMS: A REVIEW

			, go	Sul de la seconda de la second	1 00 m	10,1000	3/2		/ } 		/ } }	\ \$/\$	
Wet F	Ponds (Cont'd)												
16	McCarrons	MN	21	608.0	0.19	•	•	⊗		8		•	8
17	McKnight Basin	MN	20	725.0	0.22		•	0	•	•	8	•	8
							•	0	0	0	8	•	⊗
18	Monroe Street	WI		238.0	0.26		•	•	8	8	•	•	•
19	Runaway Bay	NC	5	437.0	0.33	•	•	⊗	⊗	8	8	8	•
20	Buckland	CT	7	20.0	0.40	•	•	8	8	•	8	•	•
21	Highway Site	FL	13	41.6	0.55	•	0	8	•	⊗	0	•	•
22	Woodhollow	TX	14	381.0	0.55	•	•	8	•	•	•	•	•
23	SR 204	WA	5	1.8	0.60	•		8	8	8	•		•
24	Farm Pond	VA		51.4	1.13	•		•	•	8	8	⊗	8
25	Burke	VA	29	27.1	1.22	8	•	•	•	8	•		•
26	Westleigh	MD	32	48.0	1.27	•	•	•	•	8	•		•
27	Mercer	WA	5	7.6	1.72	•	•	8	8	8	•	•	•
28	1-4	FL	6	26.3	2.35	•	•	8	8		8	•	
29	Timber Creek	FL	9	122.0	3.11*	•	•	•	0	•	8	8	8
30	Maitland	FL	30-40	49.0	3.65	8	8	•	8		8	•	
31	Lakeside	NC	5	65.0	7.16		Ö	8	8	8	8	8	ě

Key:

O 0 to 20% Removal

9 20 to 40% Removal

40 to 60% Removal

60 to 80% Removai80 to 100% Removai

Insufficient Knowledge

Key:

TSS Total Suspended Solids

TP Total Phosphorus

SP Soluble Phosphorus

TN Total Nitrogen

N03 Nitrate

COD Chemical Oxygen Demand

P6 Lead Zn Zinc

Note: An Asterisk (*) denotes an inferred value Note: (**)Denotes Volume of Basin/Volume of Runoff

Note: The information in the above table was taken from: A Current Assessment of Urban Best Management Practices - Techniques for Reducing Non-Point Source Pollution in the Coastal Zone, prepared by: Metropolitan Washington Council of Governments, March 1992.

THE POLLUTANT REMOVAL CAPACITY OF POND AND WETLAND SYSTEMS: A REVIEW

			40°.	M. 1000 100 100 100 100 100 100 100 100 1	S. J. S.	1000 P	3/2		 } \$/\$; 3/8	3/2	0/5/	<u> </u>
Wet E	Extended Detentio	n												
32	Uplands	ONT	5	860.0		•	•	8	8	8	8	8	8	
33	East Barrhaven	ONT		2139.0	0.12	0	•	8	⊗	8	8	8	⊗	
34	Kennedy-Burnett	ONT	6	395.0	0.62		•	⊗.	•	8	8	•	•	
Storm	water Wetlands													
35	EWA3	IL				•	•	8	8	•	8	8	•	
36	EWA4	IL				•	•	8	8	•	8	8	8	
37	EWA5	IL					•	8	8	•	⊗	8	⊗	
38	EWA6	IL						8	8		8	8	⊗	
39	B31	WA	13	461.7	0.01	0	8	8	8	0	8	⊗	8	
40	PC12	WA	13	214.0	0.03	•	8	8	8	•	⊗	8	⊗	
41	McCarrons	MN	21	608.0	0.31	•	•	8	•	8	•	•	⊗	
42	Queen Anne's	MD			0.50*	•	•	•	•	•	⊗	8	8	
43	Swift Run	MI	5	1207.0	0.60		0	•	8	•	0		8	
44	Tampa Office Pond	FL	3-8	6.3	0.61	•	•	•	8	•	0		⊗	
45	Highway Site	FL	13	41.6	0.81	•	0	⊗	•	⊗	0	•	•	
46	Palm Beach PGA	FL		2340.0	2.00°	0	•	8	8	•	8	8	⊗	

Key:

O 0 to 20% Removal

20 to 40% Removal 40 to 60% Removal

● 60 to 80% Removal 80 to 100% Removal

insufficient Knowledge

Key:

TSS Total Suspended Solids

TP Total Phosphorus

SP Soluble Phosphorus

TN Total Nitrogen

N03 Nitrate

COD Chemical Oxygen Demand

P6 Lead Zn Zinc

Note: An Asterisk (*) denotes an inferred value Note: (**)Denotes Volume of Basin/Volume of Runoff

Note: The information in the above table was taken from: A Current Assessment of Urban Best Management Practices -Techniques for Reducing Non-Point Source Pollution in the Coastal Zone, prepared by: Metropolitan Washington Council of Governments, March 1992.

THE POLLUTANT REMOVAL CAPACITY OF POND AND WETLAND SYSTEMS: A REVIEW

			/ 8	W Significant of the state of t	60 00 (2) 100 (2) (1) (1) (1) (1) (1) (1) (1) (1) (1) (1	10,10								/
Exte	nted Detention We	etlands		Tree Co.	Y LEGAL		<u> </u>	/ 6	3/2	?/ {	<u>o</u> / (3/	₹/ <i>\</i>	/
47	Benjamin Franklin			40.0	0.08	4	0	•	8	•	8	8	8	
48	Tanners's Lake	MN	10	413.0	0.10		0	Ŏ ⊗	0	0	8	•	8	
49	Mays Chapel	MD		97.0	0.10*	•	0	•	⊗	•	8	8	8	
50	Clear Lake	MN		1070.0	0.15*	•	•	•	8	8	8	8	8	
Natu	ral Wetlands													
51	Hidden Lake	FL		55.4	1.08*		0	8	8	•	8	•	•	
52	Wayzata	MN		73.0	1.25*	•	•	8	8	8	8	•	•	
Pond	/Wetland Systems	8												
53	Lake Munson	FL	3	23393.0		•	•	8	0	0	•	•	•	
						•	•	•	0	0	⊗	•	8	
54	Carver Ravine	MN	15	170.0	0.30*	•	0	0	8	0	8	0	8	
					_		•	⊗		8			8	
55	McCarrons	MN	21	608.0	>0.50			8	•	•	8	8	8	
56	Lake Jackson	FL		2230.0	0.88*		•	8	•	8	8		•	
57	Highway Site	FL	13	41.6	>1.35			8	8	⊗	8	8	8	
58	Long Lake	ME	11	18.0	2.0*									
														1

Key:

O 0 to 20% Removal

20 to 40% Removal 40 to 60% Removal

◆ 60 to 80% Removal 80 to 100% Removal

Key:

TSS Total Suspended Solids

TP Total Phosphorus

SP Soluble Phosphorus

TN Total Nitrogen

N03 Nitrate

COD Chemical Oxygen Demand

P6 Lead

Zn Zinc

Note: An Asterisk (*) denotes an inferred value Note: (**)Denotes Volume of Basin/Volume of Runoff

Note: The information in the above table was taken from: A Current Assessment of Urban Best Management Practices -Techniques for Reducing Non-Point Source Pollution in the Coastal Zone, prepared by: Metropolitan Washington Council of Governments, March 1992.